

"Express Mail" mailing label number EL 746761740 US

Date of Deposit: 10/18/01

Our Case No. 7871/13

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE  
APPLICATION FOR UNITED STATES LETTERS PATENT

INVENTOR: DAVID J. COLLODI

TITLE: PROGRAMMABLE PER-PIXEL  
SHADER WITH LIGHTING  
SUPPORT

ATTORNEY: WILLIAM F. PRENDERGAST  
BRINKS HOFER GILSON & LIONE  
P.O. BOX 10395  
CHICAGO, ILLINOIS 60610  
(312) 321-4200

## PROGRAMMABLE PER-PIXEL SHADER WITH LIGHTING SUPPORT

### BACKGROUND OF THE INVENTION

5 The present invention relates in general to the field of real-time computer generated graphics hardware. In particular, the present invention relates to the field of per-pixel shading and programmable per-pixel shading within real-time image generation devices. Until recently, most real-time 3D graphics hardware was limited to per-vertex lighting and shading operations, such as Gouraud shading and equivalents. Per-vertex operations, while computationally efficient, tend to produce visual inaccuracies for the lighting of some models and prohibit the rendering of complex surface effects such as true surface curvature, bump mapping, and proper specular reflections. More complicated effects such as Phong shading and bump mapping require that shading operations are done for substantially each drawn pixel on a polygon surface.

10 Recently, advances in hardware design and processor speed have allowed the application of a limited number of per-pixel effects to be produced in real-time graphics hardware. Recent prior art shading devices have included user-selected multi-texturing capabilities wherein end users were able to direct the texture-blending pipeline to implement a number of per-pixel effects. One such prior art approach is the implementation of Environment Mapped Bump Mapping (EMBM). In a standard EMBM implementation, 2 texture maps are provided – a bump map representing surface perturbation and an environment map representing the light from the surrounding environment. Initially, the bump map value(s) corresponding to the rendered pixel are found by addressing the bump map from interpolated vertex coordinate values. The bump map value(s) are used to compute an environment map address, which is used in turn to address the environment map. The environment map is then taken as the pixel color.

20  
25  
30 Currently, state of the art pixel shaders allow for a more involved form of user configurability. In some cases, massively parallel pixel architectures are provided consisting of a plurality of pixel processors wherein

each processor is capable of performing a user-specified sequence of instructions and mathematical operations on local data to ultimately determine pixel color. In such parallel systems, complex pixel operations can be performed quickly because the number of parallel processors can overcome the time to perform the pixel computations. However, in systems such as these, the hardware cost of supporting multiple general purpose pixel processors ultimately tends to outweigh the benefits of supporting such complex pixel operations. Other state-of-the-art programmable per-pixel shading systems provide a tighter compromise between hardwired functionality and general purpose operation by allowing a limited, user-programmable sequence of specialized pixel operations to be performed within a more traditional pixel rendering pipeline. The Microsoft DirectX8 graphics API presents a standard set of pixel operations for use in the current and future programmable per-pixel shading hardware. Compliant hardware provides for the implementation of said pixel operations, memory units to hold operation result values, and memory to hold a user-defined sequence of operations (program).

Programmable per-pixel shading architectures such as the DirectX8 compliant hardware previously described offer a great deal of user customizability while retaining the speed advantages of dedicated 3D graphics hardware. The architecture, however, provides a number of limitations as well. Most vector operations are typically limited to 8-12 bit accuracy, which is insufficient for some lighting applications such as point lighting and high order specular. Although programmable per-pixel architectures can be user-defined to perform a variety of operations, they lack parallel processing support for many general-purpose lighting calculations. While programmable architectures allow for the calculation of standard per-pixel surface normal,  $\mathbf{N}$ , and eye reflection,  $\mathbf{R}$ , vectors, using the programmable hardware to do so can waste valuable calculation and texture resources and can severely limit the accuracy of the resultant vectors. Likewise, although pixel operations may be used to perform dot product operations for standard diffuse and specular light intensity calculations, the

general purpose nature of the per-pixel operations don't lend themselves to the parallelism necessary to process multiple light sources per-pixel. Additionally, general purpose per-pixel operations offer very limited support to point lights and complex specular functions. There exists a need, therefore, for a programmable per-pixel architecture capable providing parallel processing support for general purpose lighting computations wherein the results of said lighting computations are made available for use within a user-programmable framework.

## BRIEF SUMMARY OF THE INVENTION

The present invention details a hardware extension to a programmable per-pixel shading device. The programmable shading unit is assisted by a lighting sequence unit comprising a vector generation unit, one or more point light units, one or more vector shading units and an optional accumulation unit. The vector generation unit interpolates a surface normal vector, combines it with an optional bump map vector and produces a normalized surface angle vector and a normalized view reflection vector wherein each vector may be used in the programmable unit. The point light unit supplies a normalized point light vector and a fade-off coefficient value to the programmable unit. The vector shading unit performs light-surface dot product calculations, optionally scales the dot product value and uses the scaled dot product to modify a color value. The accumulation unit combines colors into two separate channels: a diffuse color and a specular color and provides said colors for use in the programmable unit.

## BRIEF DESCRIPTION OF SEVERAL VIEWS OF THE DRAWINGS

Figure 1 is an overview of a preferred embodiment of the present invention.

Figure 2 depicts the internal components of the Lighting Sequence Unit.

Figure 2 illustrates the operation of the Vector Generation Unit.

Figure 3 shows a logic view of the operation of the Point Light Unit.

Figure 4 illustrates the operation of the Vector Shading Unit.

Figure 5 illustrates the operation of the Accumulation Unit.

## 5 DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

10 The present invention performs per-pixel calculations within real-time 3D graphics hardware. Most traditional 3D graphics hardware systems take polygonal (usually triangular) primitives, convert the primitives from world-space to screen-space if necessary, and rasterize the transformed primitive to the screen. During rasterization, the primitive is broken up into a plurality of pixels and each visible pixel is drawn to screen memory. Per-pixel processing units are used to determine pixel color before each pixel is written to screen memory. Per-pixel processing units need not necessarily operate on every pixel in the polygon or the scene as some pixels may be excluded for several reasons including but not limited to occlusion by a nearer surface. The per-pixel processing units generally determine pixel color from a combination of texture map lookups, lighting calculations, and interpolated vertex color values. Prior art per-pixel processors are capable of performing a user-programmable sequence of pixel commands which operate on pixel data to produce the final written color value. The present invention details an improved programmable per-pixel processor able to calculate per-pixel lighting effects faster and more efficiently than prior art implementations.

15 The present invention seeks to improve lighting performance by the inclusion of dedicated hardware lighting sequence processing while maintaining and enhancing user-customization by allowing said dedicated lighting hardware to provide feedback data to hardware registers which are readable (and potentially writeable) by the user-programmable sequence of pixel operations.

20 Fig. 1 presents an overview of the logic elements of a per-pixel processor that is a preferred embodiment of the present invention. Said per-pixel processor performs the same general functionality as many prior art per-

pixel processors in that it takes, as input, a number of vertex values from a rasterizer, is connected to a texture memory, and ultimately outputs a pixel color. The per-pixel processor, as with prior art approaches, operates on each drawn pixel of the rendered surface primitive. It may be desirable to increase rendering efficiency by providing multiple per-pixel processors running in parallel in order to multiply the pixel throughput. The preferred embodiment detailed herein represents only a single per-pixel processor primarily for the purpose of providing a clear example. As will be recognized by those skilled in the art, multiple copies of the processor detailed herein, as well as those of alternate embodiments, may be used in parallel within a graphics system.

As illustrated by Fig. 1, the preferred embodiment of the present invention is comprised of a Programmable Shading Unit 2 operatively connected to a texture memory 3, a rasterizer 6 and a Lighting Sequence Unit 1. The rasterizer 6, whose operation is well known to those skilled in the art, iterates through the pixels of the current polygon, optionally performs depth buffering operations and provides interpolated vertex values for each pixel. The Programmable Shading Unit 2 is responsible for executing a user-defined sequence of pixel operations. The available operations in a preferred embodiment of the present invention include, but are not limited to, operations for: using a vector value to address a texture, cube, or sphere map, calculation of a 3 or 4 dimensional dot product value, addition and subtraction of scalar and vector values, vector-scalar multiplication and division, and component-wise vector multiplication. Alternate embodiments provide different sets of pixel operations. Said pixel operations are performed on vector and scalar values stored in local memory registers. The Programmable Shading Unit has a number of registers to store scalar and vector values for per-pixel operations. Certain registers are also used to communicate data back and forth from the Lighting Sequence Unit 1. The general embodiment of the Lighting Sequence Unit illustrated in Fig. 1 contains dedicated hardware elements for the generation of normalized surface angle and reflection vectors 8, and hardware elements for the

production of light coefficient values, 9, for one or more light sources. Vertex values input from the rasterizer 6 to the Programmable Shading Unit at 7, consist of scalar or vector quantities interpolated from values given at each vertex of said polygonal primitive. The Programmable Shading unit produces a pixel color value at 5, consisting of an RGB color value or an RGBA color-alpha value.

Fig. 6 illustrates a preferred embodiment of the internal operations of the Lighting Sequence Unit. The Vector Generation Unit 71 is responsible for the calculation of a 3-dimensional, unit-length surface normal vector **N** and a 3-dimensional, unit-length view reflection vector **R**. The final **N** vector value is computed from an interpolated vertex value and is optionally perturbed by a bump map vector. The **R** vector value is found by reflecting an optionally variable view (eye) vector around the surface normal **N** vector. One or more Point Light Units 76 provide normalized point light vectors and scalar distance coefficients. One or more Vector Shading Units 74 are responsible for dot product and color scaling operations for light source color and direction vectors. An optional Accumulation Unit 75 sums two separate channels of color values to produce diffuse and specular color values. Communications between the Programmable Unit and the Lighting Sequence Unit are done, in a preferred embodiment, through shared registers. The main goal of the aforementioned hardware units is to provide parallel hardware support for commonly used lighting tasks rather than putting the burden entirely on the Programmable Shading Unit. Hardware lighting units can be assembled in a parallel, pipelined fashion to allow for a completion rate of one pixel per clock cycle. Pipelining the user-programmable operations in the Programmable Shading Unit is more difficult since the sequence of operations is variable. The use of the aforementioned hardware units is advantageous since it removes much of the burden of lighting from the Programmable Shading Unit, freeing the resources to the production of user-defined special effects. The Programmable Unit has even more flexibility since the shading values produced by the various other hardware units are made available for use within the Programmable Unit. This arrangement enhances the user

customization of shading routines while providing base per-pixel lighting at rates of 1 pixel per clock cycle or more.

Fig. 2 illustrates the operation of the Vector Generation Unit. At 11, interpolated normal data is received. Several formats of interpolated normal data may be used. In a preferred embodiment, said normal data consists of a 2-dimensional vector interpolated from polygon vertex normal vectors transformed to 2-dimensional vectors by the process described in U.S. patent application filed in the name of David J. Collodi, on January 18, 2001, bearing Serial No. 09/766,277 and entitled Method and System For Improved Per-Pixel Shading in a Computer Graphics System, the disclosure of which is hereby incorporated by reference. The interpolated normal vector may be in either fixed point or floating point format, but if a fixed point representation is used at least 12bits of accuracy are assumed. At 12, the interpolated normal vector is received and passed on to the next stage.

At 14, the interpolated normal vector is (optionally) perturbed by a bump-map vector. A bump map vector is passed in at 13. In a preferred embodiment, a 2-dimensional bump map vector is passed in from the Programmable Shading Unit. The Programmable Shading Unit may be configured to generate the bump map vector procedurally or provide the bump map vector as a result of a texture map lookup (or a combined result of multiple texture map lookups) wherein said texture map contains 2-dimensional vector values or the texture map contains height values which are subsequently converted to a two-dimensional vector value. The timing of the Programmable and Lighting Sequence Units must be configured so that the Programmable unit is able to provide a stable value at this stage of execution. Before being combined with the interpolated normal vector, the bump map vector may optionally be transformed by a 2x2 matrix supplied by the Programmable Shading Unit. The bump-map vector **b** is then combined with said interpolated normal vector **n** by vector addition to produce composite surface angle vector **c** where:

$$c = b + n$$



The **c** vector is a 2-dimensional vector that represents the surface direction of the current pixel influenced by surface curvature and (optionally) a bump map value. If bump mapping is not used for the current pixel, then the **c** vector is simply set equal to the **n** vector. The composite surface vector is output at 15.

At 17, the surface angle vector is generated from the composite surface vector **c** received at 15. A preferred embodiment uses the component values of vector **c** to address a 2-dimensional lookup table value wherein said lookup table value is used to produce substantially normalized 3-dimensional surface angle vector, **N**. The term substantially normalized is used henceforth to describe a vector whose length is in the range of 0.8 – 1.2, i.e. the vector is approximately unit length. A preferred method for obtaining a substantially normalized 3-dimensional vector from a 2-dimensional lookup table is detailed in the above-referenced U.S. patent application filed in the name of David J. Collodi, on January 18, 2001, and bearing Serial No. 09/766,277.

Alternate embodiments use dedicated hardware to directly calculate the aforementioned **N** vector from an interpolated 3-dimensional polygon vertex vector combined with a 3-dimensional bump map vector.

The normalized surface angle vector **N** is output at 19 for use within the Programmable Shading Unit. Before **N** is output, it may need to be converted to/from fixed-point format and/or reduced in accuracy dependent on the specification for the Programmable Shading Unit registers and operations. In cases where the **N** vector reduced in accuracy for output to the Programmable Shading Unit, a full precision copy of **N** is kept and used for subsequent lighting computations in the Vector Shading Units.

At 16, eye vector information is received. A preferred embodiment receives the screen coordinates for the current pixel which are then converted at 16 into a 2-dimensional offset vector, **e**. At 18, a normalized view reflection vector is generated. The 2-dimensional offset vector, **e**, is input as well as composite surface vector **c**. The **e** and **c** vectors are then combined to produce a 2-dimensional reflection vector **x**, where:

$$x = 2c + e$$

5 Next the **x** vector is used to produce substantially normalized view reflection vector **R**. The conversion of **x** to **R** may be accomplished by the aforementioned procedures used to produce the **N** vector from the **c** vector. At 20, the **R** vector is output to the Programmable Shading Unit. As with the **N** vector, a lower precision vector may be given to the Programmable Shading Unit and a full precision copy of **R** may be kept for subsequent operations. Alternate embodiments may use different algorithms for the generation of the **R** and **N** vectors provided that they are capable of ensuring a consistent format for each vector.

10 Fig 3. illustrates the operation of a single Point Light Unit, although a preferred embodiment of the present invention may contain multiple Point Light Units. At 36, point light data is received. In a preferred embodiment, said point light data consists of a 3-dimensional surface position vector, **s**, representing the position in some fixed coordinate space (such as world space or view space) of the current pixel and a point light position vector, **p**, representing the position (in the same coordinate space) of a point light. In cases where multiple Point Light Units exist, the same **s** vector is received by each unit but each unit may receive a separate **p** vector. At 30, non-normalized point light vector, **l**, is generated where:

$$l = p - s$$

25 At 31, scalar distance-squared value, **d**, is calculated where:

$$d = l \bullet l$$

30 At 32, normalized light vector, **P**, is calculated by normalizing the **l** vector. The normalization of the **l** vector is performed, in a preferred manner, by the operations detailed in above-referenced U.S. patent application filed in

the name of David J. Collodi, on January 18, 2001, and bearing Serial No. 09/766,277. However, since the **I** vector can vary drastically in length, it may be desirable to scale the **I** vector before normalization. The substantially normalized point light vector, **P**, is output at 34.

At 33 a distance scalar value, **h**, is calculated where:

$$h = \frac{c}{d}$$

where **c** is a user selected scalar value. It may be desirable to clamp the **d** value to a lower bound of 1 before calculating the **h** value. The **h** value represents the intensity of light at the surface point associated with the current pixel. At 35, said distance scalar value, **h**, is output. In a preferred practice of the present invention, the **P** vector is output as a 4-dimensional vector with the **h** value used as the 4<sup>th</sup> vector component.

Fig. 4 illustrates the operation of the Vector Shading Unit. At 41 and 42, a light vector, **L**, and surface vector, **S**, are input. The light vector may be a user-provided light vector or a point light vector generated from the Point Light Unit. As a preferred practice of the present invention, it is assumed that the **L** vector is a 4-dimensional vector value where the 4<sup>th</sup> vector component consists of the aforementioned scalar **h** value in the case of a point light vector and consists of a user defined scalar value (usually, but not necessarily, 1.0) in the case of a user-provided light vector. The surface vector, **S**, typically consists of either the surface angle vector, **N**, or the view reflection vector, **R**, output by the Vector Generation Unit as previously detailed. However, a user-provided **S** value may also be used. In either case, the **S** vector is assumed to be a 4-dimensional vector value. In the case where the **S** vector is taken as the **N** or **R** vectors, as previously described, a value of 1.0 may be taken as the 4<sup>th</sup> vector component to assure that **S** is a 4-dimensional vector. In a preferred embodiment, the Vector Shading Unit may be programmed to received the **L** and **S** vectors from user-specified hardware registers wherein said registers may be either special-purpose registers

designated to hold the output vectors of the Point Light/Vector Generation Units or general-purpose registers in the Programmable Shading Unit.

At 46, a raw scalar dot product value,  $r$ , is calculated where:

$$r = L \bullet S$$

The  $r$  value may be provided for use in the Programmable Shading Unit at 46. At 44, the raw dot product value,  $r$ , is optionally scaled. The purpose of this stage is primarily to incorporate the effects of shadows and surface specularity functions. Two scalar values,  $y$  and  $z$ , may be user-provided. A 2-dimensional specular map may also be specified wherein said map may reside in texture memory or local shader memory. The  $r$  and  $y$  values are used as a coordinate pair  $(r,y)$  to address said specular map which provides a scalar value  $w$ . If a specular map is not used, the  $w$  value is set equal to  $r$ . The  $w$  value is then multiplied by the  $z$  value producing the scaled dot product value  $q$ . At 47, the  $q$  value is provided for use in the Programmable Shading Unit. At 45, a 3 or 4-dimensional color vector  $c$  is scaled by said  $q$  value. Said color vector is user-provided through the Programmable Shading Unit, i.e., a general or special-purpose register may be used to hold said color vector. A resulting color vector  $e$  is calculated where:

$$e = qc$$

The  $e$  value is output at 48.

An alternate embodiment implements the Point Light Unit and Vector Shading Unit as fully programmable hardware elements wherein the sub-tasks of said hardware units may be executed independently through commands from the Programmable Shading Unit. The Point Light and Vector Shading Units should be designed to provide a throughput rate of one operation per clock cycle provided their subtasks operations are performed in a pre-defined sequence.

Fig. 5 illustrates the operations of the Accumulation Unit. The Accumulation Unit is responsible for the combination of specular and diffuse light colors. At 55, one or more diffuse color vectors are input wherein said color vectors are 3 or 4-dimensional vector values. In a preferred practice of the present invention, the Accumulation is configurable to receive diffuse color vectors from a user-defined set of general or special purpose registers. At 59, said diffuse color vectors are combined through vector addition to produce a combined diffuse color vector. Said combined diffuse color vector is output at 57. At 56, one or more specular color vectors are input. At 60, said specular color vectors are combined through vector addition producing a combined specular color vector which is output at 58. Alternate embodiments exclude the Accumulation Unit and allow the user to combine diffuse and specular colors through the Programmable Shading Unit.

After the combined diffuse and specular color vectors are arrived at, the user may use them to modify the pixel color in the Programmable Shading Unit. A preferred embodiment provides dedicated hardware to perform a component-wise multiplication of a surface color vector and the combined diffuse color vector followed by the addition of the combined specular color value. Using dedicated hardware for this task, as opposed to general purpose Programmable Shading operations, allows a standard pixel lighting sequence to be completed at a rate of one pixel per clock cycle (or higher). Alternate embodiments use general purpose Programmable Shading operations to perform diffuse and specular light combination.

The pixel color may be further modified, i.e., to incorporate fogging effects, or directly output from the Programmable Shading Unit as the final pixel color. Practices of the present invention have allowed for configurable per-pixel lighting at rates of one pixel per clock cycle or higher to be achieved in real-time 3D graphics hardware.

The detailed description presented herein is primarily for the purposes of example and, as should be recognized by those skilled in the applicable art, changes and modifications may be made to disclosed implementation without departing from the scope of the present invention as defined by the appended claims and their equivalents.

5

11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100  
101  
102  
103  
104  
105  
106  
107  
108  
109  
110  
111  
112  
113  
114  
115  
116  
117  
118  
119  
120  
121  
122  
123  
124  
125  
126  
127  
128  
129  
130  
131  
132  
133  
134  
135  
136  
137  
138  
139  
140  
141  
142  
143  
144  
145  
146  
147  
148  
149  
150  
151  
152  
153  
154  
155  
156  
157  
158  
159  
160  
161  
162  
163  
164  
165  
166  
167  
168  
169  
170  
171  
172  
173  
174  
175  
176  
177  
178  
179  
180  
181  
182  
183  
184  
185  
186  
187  
188  
189  
190  
191  
192  
193  
194  
195  
196  
197  
198  
199  
200  
201  
202  
203  
204  
205  
206  
207  
208  
209  
210  
211  
212  
213  
214  
215  
216  
217  
218  
219  
220  
221  
222  
223  
224  
225  
226  
227  
228  
229  
230  
231  
232  
233  
234  
235  
236  
237  
238  
239  
240  
241  
242  
243  
244  
245  
246  
247  
248  
249  
250  
251  
252  
253  
254  
255  
256  
257  
258  
259  
260  
261  
262  
263  
264  
265  
266  
267  
268  
269  
270  
271  
272  
273  
274  
275  
276  
277  
278  
279  
280  
281  
282  
283  
284  
285  
286  
287  
288  
289  
290  
291  
292  
293  
294  
295  
296  
297  
298  
299  
300  
301  
302  
303  
304  
305  
306  
307  
308  
309  
310  
311  
312  
313  
314  
315  
316  
317  
318  
319  
320  
321  
322  
323  
324  
325  
326  
327  
328  
329  
330  
331  
332  
333  
334  
335  
336  
337  
338  
339  
340  
341  
342  
343  
344  
345  
346  
347  
348  
349  
350  
351  
352  
353  
354  
355  
356  
357  
358  
359  
360  
361  
362  
363  
364  
365  
366  
367  
368  
369  
370  
371  
372  
373  
374  
375  
376  
377  
378  
379  
380  
381  
382  
383  
384  
385  
386  
387  
388  
389  
390  
391  
392  
393  
394  
395  
396  
397  
398  
399  
400  
401  
402  
403  
404  
405  
406  
407  
408  
409  
410  
411  
412  
413  
414  
415  
416  
417  
418  
419  
420  
421  
422  
423  
424  
425  
426  
427  
428  
429  
430  
431  
432  
433  
434  
435  
436  
437  
438  
439  
440  
441  
442  
443  
444  
445  
446  
447  
448  
449  
450  
451  
452  
453  
454  
455  
456  
457  
458  
459  
460  
461  
462  
463  
464  
465  
466  
467  
468  
469  
470  
471  
472  
473  
474  
475  
476  
477  
478  
479  
480  
481  
482  
483  
484  
485  
486  
487  
488  
489  
490  
491  
492  
493  
494  
495  
496  
497  
498  
499  
500  
501  
502  
503  
504  
505  
506  
507  
508  
509  
510  
511  
512  
513  
514  
515  
516  
517  
518  
519  
520  
521  
522  
523  
524  
525  
526  
527  
528  
529  
530  
531  
532  
533  
534  
535  
536  
537  
538  
539  
540  
541  
542  
543  
544  
545  
546  
547  
548  
549  
550  
551  
552  
553  
554  
555  
556  
557  
558  
559  
560  
561  
562  
563  
564  
565  
566  
567  
568  
569  
570  
571  
572  
573  
574  
575  
576  
577  
578  
579  
580  
581  
582  
583  
584  
585  
586  
587  
588  
589  
590  
591  
592  
593  
594  
595  
596  
597  
598  
599  
600  
601  
602  
603  
604  
605  
606  
607  
608  
609  
610  
611  
612  
613  
614  
615  
616  
617  
618  
619  
620  
621  
622  
623  
624  
625  
626  
627  
628  
629  
630  
631  
632  
633  
634  
635  
636  
637  
638  
639  
640  
641  
642  
643  
644  
645  
646  
647  
648  
649  
650  
651  
652  
653  
654  
655  
656  
657  
658  
659  
660  
661  
662  
663  
664  
665  
666  
667  
668  
669  
670  
671  
672  
673  
674  
675  
676  
677  
678  
679  
680  
681  
682  
683  
684  
685  
686  
687  
688  
689  
690  
691  
692  
693  
694  
695  
696  
697  
698  
699  
700  
701  
702  
703  
704  
705  
706  
707  
708  
709  
710  
711  
712  
713  
714  
715  
716  
717  
718  
719  
720  
721  
722  
723  
724  
725  
726  
727  
728  
729  
730  
731  
732  
733  
734  
735  
736  
737  
738  
739  
740  
741  
742  
743  
744  
745  
746  
747  
748  
749  
750  
751  
752  
753  
754  
755  
756  
757  
758  
759  
760  
761  
762  
763  
764  
765  
766  
767  
768  
769  
770  
771  
772  
773  
774  
775  
776  
777  
778  
779  
780  
781  
782  
783  
784  
785  
786  
787  
788  
789  
790  
791  
792  
793  
794  
795  
796  
797  
798  
799  
800  
801  
802  
803  
804  
805  
806  
807  
808  
809  
810  
811  
812  
813  
814  
815  
816  
817  
818  
819  
820  
821  
822  
823  
824  
825  
826  
827  
828  
829  
830  
831  
832  
833  
834  
835  
836  
837  
838  
839  
840  
841  
842  
843  
844  
845  
846  
847  
848  
849  
850  
851  
852  
853  
854  
855  
856  
857  
858  
859  
860  
861  
862  
863  
864  
865  
866  
867  
868  
869  
870  
871  
872  
873  
874  
875  
876  
877  
878  
879  
880  
881  
882  
883  
884  
885  
886  
887  
888  
889  
890  
891  
892  
893  
894  
895  
896  
897  
898  
899  
900  
901  
902  
903  
904  
905  
906  
907  
908  
909  
910  
911  
912  
913  
914  
915  
916  
917  
918  
919  
920  
921  
922  
923  
924  
925  
926  
927  
928  
929  
930  
931  
932  
933  
934  
935  
936  
937  
938  
939  
940  
941  
942  
943  
944  
945  
946  
947  
948  
949  
950  
951  
952  
953  
954  
955  
956  
957  
958  
959  
960  
961  
962  
963  
964  
965  
966  
967  
968  
969  
970  
971  
972  
973  
974  
975  
976  
977  
978  
979  
980  
981  
982  
983  
984  
985  
986  
987  
988  
989  
990  
991  
992  
993  
994  
995  
996  
997  
998  
999  
1000